







## AT-1 MULTI-PURPOSE OIL, 1000, 2810, 2820, 2830, 2835, 2840



*Multi-purpose oil that displaces moisture, lubricates and prevents oxidation and corrosion. Removes moisture from electrical appliances. Forms a thin protecting film. Regular usage guarantees the reliable operation of machinery and equipment. Features: flash point +68 °C , boiling point +200 °C, specific gravity 0.8104 5 %, salt spray test for 16 hours: no rust, coverage capacity 79m<sup>2</sup>/l, the humidity cabinet test 1200 h: no rust, protection film thickness 1.8 microns. Meets MIL-C-23411 and MIL-C-16173D requirements, grade 3. Non-volatile oils 12.2 %.*

| Article number | Package size | Package      | Batch/PCS | UN-code | EAN-code   |
|----------------|--------------|--------------|-----------|---------|--|
| 1000           | 100/140 ml   | aerosol      | 24        | 1950    | <br>6 416631 010006  |
| 2810           | 400/520 ml   | aerosol      | 12        | 1950    | <br>6 416631 028100 |
| 2820           | 5 l          | tin canister | 1         |         | <br>6 416631 028209 |
| 2830           | 10 l         | tin canister | 1         |         | <br>6 416631 028308 |
| 2835           | 25 l         | tin canister | 1         |         | <br>6 416631 028353 |
| 2840           | 200 l        | barrel       | 1         |         | <br>6 416631 028407 |