AT-3 RUST INHIBITOR AND LUBRICANT, 3000, 3010, 3015, 3020, 3030



Effectively protects against corrosion, even in difficult conditions. Displaces moisture and leaves a waxy, lubricating film. Truly effective protective agent for the long-term storage of machinery and equipment: for outdoor storage as well as storage during sea shipping. Meets the following MIL-standards: non-volatile oils: 48.0 % MIL-C-0083933A (MR) and MIL-PFR 16173E grade 4, class 1, Ford M-7-C-16A, P.O.D.V-5-65, MIL-C-62218 (AT). Features: flash point +43 °C , boiling point +150 °C, specific gravity 0.8700 5 %, salt spray test for more than 1,440 hours: no rust, coverage capacity 13.5 m²/l, the humidity cabinet test over 1,440 h: no rust, protection film thickness 27.0 microns. Applications: industry, ships, aircraft, trucks, construction equipment, cranes, agricultural combines and implements, in cars, e.g. battery terminals as well as electrical connectors of car trailers and caravans, AT-3 is suitable as a protective and lubricant for all types of chains and conveyors .

Article number	Package size	Package	Batch/PCS	UN-code	EAN-code
3000	400/520 ml	aerosol	12	1950	6 416631 030004
3010	5 l	tin canister	1		6 416631 030103
3015	10 l	tin canister	1		6 416631 030158
3020	25 l	tin canister	1		6 416631 030202
3030	200 l	barrel	1		6 416631 030301